

DIAGNOSTICPRO[®] Advantage

For PACS & Remote Primary Diagnosis



The VIDAR Advantage

VIDAR[®] Systems Corporation — the recognized leader in film digitizing technology — offers the VIDAR DiagnosticPRO[™] Advantage Film Digitizer. VIDAR again has raised the bar with its new Advantage product platform by achieving better overall performance than any other digitizer on the market.

VIDAR's DiagnosticPRO Advantage film digitizer has achieved the highest reliability, image quality, consistency, and best overall productivity than any other digitizer on the market.

- MTBF \geq 50,000
- Superior image quality
- Exceptional consistency
- Increased speed

Technology Advantage and Innovation

The next generation DiagnosticPRO Advantage has a number of technological advances that will provide customers with increased “up-time”, resulting in improved productivity and revenues. Higher speed, image quality, and reliability are just some of the new features of the DiagnosticPRO Advantage. With a Mean Time Between Failure (MTBF) rate of \geq 50,000 hours, a modular film feeder, and a field replaceable illuminator system (Instant-On VIDAR Hot Light[™]), these technical advances have resulted in the highest reliability of any digitizer on the market. A number of patents have been filed based on these technical innovations that have set a new standard in medical film digitizer performance.

Provides customers increased “up-time” resulting in improved productivity and revenues

In addition to a higher level of image quality and more consistency, the DiagnosticPRO Advantage has been designed for increased speed. It digitizes film two times faster than previous models and will digitize up to 25 mixed-sized films in batch mode, allowing more productivity and greater efficiency — key benefits for radiology department personnel. The DiagnosticPRO Advantage features the company's proprietary High Definition CCD (HD-CCD[®]) technology, and incorporates a substantially more sophisticated HD-CCD array and digital electronics design. Also, the unique ADC[™] (Automatic Digitizer Calibration) that prompts the film digitizer to calibrate automatically before every film digitized, and eliminates the need for user intervention for this operation. VIDAR's ADC feature results in virtually no variation in image quality and



ensures excellent grayscale reproduction in every image.

The DiagnosticPRO Advantage, with its high-resolution capabilities (44.5 microns), provides the ability to digitize mammography films, and offers larger spot size options for digitizing general radiographic, CT, MR, ultrasound, and nuclear medicine films. The DiagnosticPRO Advantage exceeds the American College of Radiology Teleradiology Practice Guidelines. In addition, VIDAR offers the only 32-bit data path in the industry to maximize grayscale accuracy and performance.

Exceptional Consistency — Proven Reliability

Unlike other digitizers that require biannual calibration or cleaning, VIDAR digitizers need no maintenance or calibration, saving nearly \$2,000 annually. The straight-line film path reduces the need for costly service calls due to film jams, and VIDAR digitizers have a MTBF of more than five years.

The company's sole focus is on serving its customers, and a premier customer service department supports VIDAR digitizers. VIDAR works hard at customer satisfaction, and customers have responded enthusiastically, giving VIDAR the highest customer satisfaction rating in the industry.

DIAGNOSTICPRO[®] Advantage



Nominal Resolution	Pixels (14"x17" film)	Spot Size (um)	DPI	Line pairs Per mm	Digitizing Speed
2K x 2.5K*	2002 x 2431	170	150	3	12 Seconds
4K x 5K	3990 x 4845	85	300	6	24 Seconds
Mammography film: 18 cm x 24 cm					
4K x 5K	4104 x 5472	44	570	11	20 Seconds

*ACR Standard for Teleradiology Guidelines [Revision 35 (1998)] recommends 2.5 line pairs/mm minimum

Clinical Optical Density Range	.05 to 4.0
Bit Depth	32-bit mapped to 12-bit (4096) and 8-bit (256) grayscale output
MTBF	≥50,000 hours
Film Sizes	Width: 8" to 14" (20 cm to 35.6 cm) Length: 8" to 51" (20 cm to 129.5 cm in single film mode only) Thickness: 0.006" to 0.008
Auto Film Feeder	Standard 25-film capacity (mixed sized – no presorting necessary) "Light Box" loading: head-up, normal reading, left justified Film sizes up to 14" x 17" (35.6 cm x 43.2 cm)
Translation Tables	Linear OD
Geometric Accuracy	Better than 1% or 2 pixels, whichever is greater, in both axes
Scan Rate	200 lines/second
Hardware Interface	USB 2.0
Software	Windows [®] scanning modules and software development tools available
Power Requirements	Voltage: 85~264 Vac Frequency: 47~63 Hz Power: ≤100 Watts
Operating Environment	50° to 95° F (10° to 35° C), 20% to 85% relative humidity, non-condensing
Storage Environment	0° to 140° F (-18° to 60° C), 20% to 85% relative humidity, non-condensing
Illuminator	Instant-On VIDAR Hot Light™ Technology; ≥100,000 scans
Detector	Solid-state, next-generation High Definition CCD (HD-CCD [®])
Dimensions	With Feeder & Exit Tray: 19" W x 23" D x 29.25" H (483mm x 584mm x 743 mm) Without Feeder & Exit Tray: 19" W x 14.25 D" x 16.5" H (483mm x 362mm x 419mm) Shipping: 24" W x 29" L x 24" H (610mm x 737mm x 610mm)
Weight	40 lbs. (18 kg); shipping weight: 60 lbs. (27 kg)
Certifications	FDA Class II 510(k) 993599; CE-MDD 93/42/EEC Class 1; CAN/CSA C22.2 No 601.1-M90; Health Canada Class II; Japan-MHW; CCC; SFDA; KFDA; FCC Class A; EN 60601-1-2; IEC 60601-1; IEC 60950; ISO 9001:2000; ISO 13485:2003

Specifications are subject to change without notice.

365 Herndon Parkway
Herndon, VA USA 20170
www.filmdigitizer.com

Phone: +1.703.471.7070
Toll-Free: 1.800.471.7226
Fax: +1.703.471.7600



Dealer Information

A Walsh Imaging, Inc.
55 Cannonball Road
Pompton Lakes, NJ 07442

Phone 1-866-429-9729
Web www.awalshimaging.com

VIDAR and HD-CCD are registered trademarks of VIDAR Systems Corporation. ADC and Digitizer are registered trademarks of ADC Systems Corporation. All other product names are registered marks of their respective owners.

VIDAR Publication PN 15787-001, Rev E, January 2006